



Pump Dimension

Product Model (Secondary MotorType)	Rated Flow (m <sup>3</sup> /h)	Rated head (m)	Power (kw)	Voltage (v)	Speed (r/min)	Dimensions (mm)								Gross weight (kg)	Packing size length * width * height (cm)
						H	H1	H2	D2	B2	B3	L5	d		
80WQ40-9-2.2S	40	9	2.2	380	2850	555	385	120	215	263	388	231	80	40.5	58*22*26
50WQ15-25-3S	15	25	3	380	2850	605	435	130	230	255	350	225	50	43	63*24*28
65WQ25-18-3S	25	18	3	380	2850	605	435	130	230	265	370	227	65	44	63*24*28
80WQ40-13-3S	40	13	3	380	2850	605	435	130	230	275	400	245	80	45	63*24*28
50WQ15-32-4S	15	32	4	380	2850	670	480	155	270	330	425	260	50	55.5	72*28*33
65WQ25-26-4S	25	26	4	380	2850	670	480	155	270	330	435	262	65	57.5	72*28*33
80WQ40-18-4S	40	18	4	380	2850	670	480	155	270	330	455	280	80	61.5	72*28*33
100WQ50-13-4S	50	13	4	380	2850	680	490	160	270	330	480	302	100	64.5	72*28*33
50WQ15-40-5.5S	15	40	5.5	380	2850	730	530	155	270	330	435	260	50	66	72*28*33
50WQ25-32-5.5S	25	32	5.5	380	2850	730	530	155	270	330	425	260	50	66.5	72*28*33
65WQ30-27-5.5S	30	27	5.5	380	2850	730	530	155	270	330	435	260	65	68	80*28*33
80WQ50-18-5.5S	50	18	5.5	380	2850	730	530	155	270	330	455	280	80	73	80*28*33
100WQ70-15-5.5S	70	15	5.5	380	2850	740	540	160	270	330	480	302	100	76	80*28*33
150WQ100-8-5.5S	100	8	5.5	380	2850	760	560	175	280	368	560	350	150	81	86x35x40
50WQ20-40-7.5S	20	40	7.5	380	2850	810	640	200	315	325	410	258	50	91	86x35x40
65WQ30-32-7.5S	30	32	7.5	380	2850	810	640	200	315	325	420	260	65	93	86x35x40
80WQ45-22-7.5S	45	22	7.5	380	2850	820	650	210	315	360	485	315	80	95	86x35x40
100WQ80-20-7.5S	80	20	7.5	380	2850	820	650	210	315	360	510	335	100	96	86x35x40
150WQ100-15-7.5S	100	15	7.5	380	2850	820	650	215	315	395	590	360	150	98	86x35x40
50WQ20-50-11S	20	50	11	380	2850	810	640	200	315	325	410	258	50	103	40x35*96
65WQ50-40-11S	50	40	11	380	2850	810	640	200	315	325	410	258	65	106	40x35*97
80WQ70-35-11S	70	35	11	380	2850	820	650	210	315	360	485	315	80	107	40x35*98
100WQ100-25-11S	100	25	11	380	2850	820	650	210	315	360	510	335	100	108	40x35*99
150WQ180-11-11S	180	11	11	380	2850	820	650	215	315	395	590	360	150	110	40x35*100
50WQ20-55-15S	20	55	15	380	2850	810	640	200	315	325	410	258	50	111	40x35*101
65WQ45-50-15S	45	50	15	380	2850	810	640	200	315	325	410	258	65	114	40x35*102
80WQ80-32-15S	80	32	15	380	2850	820	650	210	315	360	485	315	80	115	40x35*103
100WQ120-25-15S	120	25	15	380	2850	820	650	210	315	360	510	335	100	116	40x35*104
150WQ180-15-15S	180	15	15	380	2850	820	650	215	315	395	590	360	150	118	40x35*105

Performance Curve

